

**atp di F. Garzoni**

I - 25074 LAVENONE - BS - ITALY

via del Tram, 8

P.Iva P.Iva IT00232730986

FAX +39 0365 823054

www.atp.it - info@atp.it

**Update: 01-10-2022 10:41:00**

articoli tecnici per l'industria e la casa

termoplastici e metalli

**industrial and housing technical items**

**thermoplastic and metal**



## **CATALOGUS - MA - Deur- en raamkrukdonderdelen**



Onze online catalogus op [www.atp.it](http://www.atp.it) wordt constant actueel gehouden.



Index (in volgorde van verschijning in catalogus):

- Tilt & Turn roses for windows (4-8 positions)

**Quantità minima d'ordine = 1 confezione**

**Le misure e i pesi indicati nel catalogo si intendono nominali.**

**Le descrizioni tra uguali (= =) sono versioni speciali senza disponibilità immediata a magazzino.**

**Lo scarto fino ad un 1% è da considerarsi fisiologico.**

Positie Artikelcode	Beschrijving	Materiaal	Kleur Finish	Verpakking Omverpakk.
808.g MKDV246D16/0001		polyamide polyacetaal ijzer	neutraal	250 x doos 250
809.g MKDV246D16/0101		polyamide polyacetaal ijzer	neutraal	250 x doos 250
810.g MKDV246K16/0001	Oval 8 position rosette 24x60x6 mm, screw holes without nuts, with zinc-plated spindle square 7x8x70 mm, square 8 mm over-coated, spindle length on handle side -A- 28 mm, on window side -B- 40 mm	polyamide polyacetaal ijzer	neutraal	250 x doos 250
		Si abbinare: alle rosette ovali 24x60x6 da pos. <b>800.a</b> e rettangolari da pos. <b>803.a.05</b>		
811.b MKDV246K16/0301	Oval 8 position rosette 24x60x6 mm, screw holes with nuts, with zinc-plated spindle square 7x8x61 mm, square 8 mm over-coated, spindle length on handle side -A- 28 mm, on window side -B- 31 mm	polyamide polyacetaal ijzer	neutraal	250 x doos 250
811.g MKDV246K16/0101	Oval 8 position rosette 24x60x6 mm, screw holes with nuts, with zinc-plated spindle square 7x8x70 mm, square 8 mm over-coated, spindle length on handle side -A- 28 mm, on window side -B- 40 mm	polyamide polyacetaal ijzer	neutraal	250 x doos 250
		Si abbinare: alle rosette ovali 24x60x6 da pos. <b>800.a</b> e rettangolari da pos. <b>803.a.05</b>		